

## Credit

### patents



### certifications



ISO 9001 : 2015  
ISO 14001 : 2015  
ISO 45001: 2018

Korean's don't put up with ramen  
Right now, LAZO

Now, let's cook  
**Han-River ramen** with LAZO

eats\_lazo

lazo.kr

@eatslazo

**Inquiry**

ideainfo@myidea.kr

idea **IDEA Co.,Ltd.**

Room 501, 20-38 Mugunghwa-ro, Ilsan-dong-gu,  
Goyang-si, Gyeonggi-do, Korea

Make a LAZO Life

Instant noodle cooker

**LAZO**



**Life & Joy**

**LAZO-single**

*Life*

Help your life,  
**smart-LAZO**

Convenience store, Tea making room



### spec

Voltage	220~240V, 50/60HZ	120V, 60HZ
Power Consumption	1500W	1800W
Size	24.5cm(front)×42.5cm(side)×40.5cm(height)	
Exterior Material	Heat-resistant plastics	
Weight	Worktop : Heat-resistant tempered glass 5.9kg	
Main Components	Electric water heater : 1L	Power consumption : 600W Hot water quantity : 1L
	Heater~Power consumption:900W	1200W
	PCBA	
	Control panel	
	Solenoid valve	
Safety System	Motor	Option
	Overheating prevention sensor	
	Overheating prevention temperature fuse	
	Overheating prevention bimetal	
IPX Waterproof	IPX 1	
Rated Capacity	1L	
Rated Pressure	MAX 196 kPa, Min 49kPa	

**Container**

Safe dedicated containers  
that have obtained test reports



**Size**  
115×115×60(mm)  
**Material**  
Paper+Aluminum+PET  
**Applicable Models**  
single, double



**Size**  
190×170×70(mm)  
**Material**  
Paper+Aluminum+PET  
**Applicable Models**  
single, double



**Size**  
135×135×55(mm)  
**Material**  
Aluminum (above 99.8%)  
**Applicable Models**  
single, double

• Customizable, Put advertisements in paper containers

**LAZO-double**

*Joy*

Enjoy at double,  
**joyful-LAZO**

Han-River park, Campground, Franchise store



### spec

Size	48cm(front)×43.1cm(side)×47.5cm(height)	
Exterior Material	SCP1-SD	
Weight	Worktop : Heat-resistant tempered glass 18kg	
Main Components	Electric water heater : 2L	Power consumption : 1.0kw Hot water quantity : 2L
	Heater~Power consumption : 1.7kw	
	PCBA	
	Control panel	
	Solenoid valve	
Safety System	Motor	Option
	Overheating prevention sensor	
	Overheating prevention temperature fuse	
	Overheating prevention bimetal	
Voltage	220V~240V~, 50/60Hz	
Power Consumption	2.7kw	
IPX Waterproof	IPX 1	
Rated Capacity	2L	
Rated Pressure	0.6MPa	