Credit

patents





certifications











ISO 9001: 2015

ISO 14001: 2015 ISO 45001: 2018 Make a LAZO Life

Now, let's cook Han-River ramen with LAZO

Korean's don't put up with ramen

Right now, LAZO

lazo_global



lazo.kr



@eatslazo

Inquiry

ideainfo@myidea.kr

IDÉA Co.,Ltd.

Room 501, 20-38 Mugunghwa-ro, Ilsan-dong-gu, Goyang-si, Gyeonggi-do, Korea

ideA



Instant noodle cooker

LAZO

Life&Joy

LAZO-single

Help your life, smart-LAZO



LAZO

Convenience store, Tea making room



spec

	Voltage	220-240V, 50/60HZ	120V, 60HZ
	Power Consumption	1500W	1800W
	Size	24.5cm(front)×42.5cm(side)×40.5cm(height)	
	Exterior Material	Heat-resistant plastics	
		Worktop: Heat-resistant tempered glass	
	Weight	5.9kg	
	Main Components	Electric water heater : 1L	Power consumption: 600W
			Hot water quantity : 1L
		Heater-Power consumption:900W	1200W
		PCBA	
		Control panel	
		Solenoid valve	
		Motor	Option
	Safety System	Overheating prevention sensor	
		Overheating prevention temperature fuse	
		Overheating prevention bimetal	
	IPX Waterproof	IPX 1	
	Rated Capacity	1L	
	Rated Pressure	MAX 196 kPa, Min 49kPa	

Container

Safe dedicated containers that have obtained test reports



Size 115×115×60(mm) Material Paper+Aluminum+PET Applicable Models

single, double



Size 190×170×70(mm) Paper+Aluminum+PET Applicable Models single, double



Size 135×135×55(mm) Aluminum (above 99.8%) single, double

• Customizable, Put advertisements in paper containers

LAZO-double

Enjoy at double, joyful-LAZO



Han-River park, Campground, Franchise store



spec

Size	48cm(front)×43.1cm(side)×47.5cm(height)		
Exterior	SCP1-SD		
Material	Worktop: Heat-resistant tempered glass		
Weight	18kg		
Main Components	Electric water heater : 2L	Power consumption: 1.0kw	
		Hot water quantity : 2L	
	Heater-Power consumption : 1.7kw		
	PCBA		
	Control panel		
	Solenoid valve		
	Motor	Option	
Cafala	Overheating prevention sensor		
Safety System	Overheating prevention temperature fuse		
Jystem	Overheating prevention bimetal		
Voltage	220V-240V~, 50/60Hz		
Power Consumption	2.7kw		
IPX Waterproof	IPX 1		
Rated Capacity	2L		
Rated Pressure	0.6MPa		